## LIST OF FIGURES

Figure	<u>Title</u>
2-1	Containment Dome Geometry
2-2	Construction Sequence
2-3	Tendon Layout
3-1	Dome Coring Results
3-2	Contours of Deepest Delaminations
3-3	Tendon Liftoff Values
3-4	Instrumentation Locations
3-5	Sensor ID 42
3-6	Sensor ID 82
3-7	Sensor ID 63
3-8	Sensor ID 43
3-9	Sensor ID 20
3-10	Sensor ID 64
3-11	Sensor ID 44
3-12	Sensor ID 84
3-13	Sensor ID 21
3-14	Sensor ID 85
3-15	Sensor ID 22
3-16	Sensor ID 66
3-17	Sensor ID 417
3-18	Sensor ID 418
3-19	Sensor ID 419
3-20	Sensor ID 420
3-21	Coring on Construction Joints
3-22	Coring After Concrete Removal
3-23	Contours of Deepest Delaminations Verified By Concrete Removal and Coring
3-24	Sections Showing Delaminations

3-25	Sections Showing Delaminations
3-26	East Side of Dome During Concrete Removal
3-27	West Side of Dome During Concrete Removal
3-28	Detailed Pictures of Concrete Removal
3-29	Detailed Pictures of Concrete Removal
4-1	Concrete Specimens
5-1	Crane Location
5-2	Thermal Gradient
5-3	Radial Tension
5-4	Unbalanced Loads From Post-Tensioning
5-5	Loading Areas
5-6	Meridional Stress at the Outer Surface From Dome Post-Tensioning
5-7	Circumferential Stress at the Outer Surface From Dome Post-Tensioning
5-8	Meridional Stress at the Outer Surface From Dome Post-Tensioning
5-9	Circumferential Stress at the Outer Surface From Dome Post-Tensioning
5-10	Nonuniform Bearing Case 1
5-11	Nonuniform Bearing Case 2
5-12	Plexiglass Dome Without Load
5-13	Plexiglass Dome With Load
5-14	Axisymmetrical Simulation of the Meridional Construction Joint
5-15	Meridional Stresses at the Outside Surface From the Post-Tensioning Load at 50% Completion. All Joints Assumed Hinged With Membrane Forces Acting at Center of Section.
5-16	Circumferential Stresses at the Outside Surface From the Post-Tensioning Load at 50% Completion. All Joints Assumed Hinged With Membrane Forces Acting at Center of Section.

Title

Figure

Figure	<u>Title</u>
5-17	Meridional Stresses at the Outside Surface From the Post-Tensioning Load at 50% Completion. All Joints Assumed Hinged With the Membrane Forces Acting at the Top of the Circumferential and Meridional Joints.
5-18	Circumferential Stresses at the Outside Surface From the Post-Tensioning Load at 50% Completion. All Joints Assumed Hinged With the Membrane Forces Acting at the Top of the Circumferential and Meridional Joints.
6-1	Compatibility Analytical Model
6-2	Compatibility Analysis Stress Distribution
6-3	Compatibility Analysis Stress Distribution
6-4	Compatibility Analysis Stress Distribution
6-5	Illustration of Concrete Removal Area
6-6	Illustration of Concrete Anchors
6-7	Illustration of Typical Instrumentation
6-8	Illustration of Concrete Replacement